

GR 1 GRAFFITI REMOVER FOR BRICK ,STONE, CONCRETE,WOOD.

An easy to use liquid graffiti remover with deep penetration and fast acting power for exterior surfaces. GR 1 Graffiti remover penetrates and loosens spray paint graffiti and allows for easy removal of the graffiti from the surface.

It is specifically formulated for use on masonry, brick, concrete, stone, mild steel, stainless steel, painted surfaces and wooden surfaces.(do not use GR1 Graffiti Remover on plastic, galvanized metal surfaces or non-ferrous metal surfaces such as aluminum)

Exterior Graffiti removal process for un-painted surfaces:

- 1: Put on your protective clothing, safety goggles and gloves
- 2: Check the surface for excess dirt: The surface does not have to be perfectly clean but if there is a lot of traffic film, soot or substantial dirt, it is advisable to clean or power wash this off first.
- 3: Test a small hidden area prior to full application
- 4: **Shake the product thoroughly** to activate it and pour required amount into polypropylene container
- 5: Apply with brush or roller starting from the top
- 6: wait about 90 seconds then pressure wash off from the bottom up
- 7: repeat steps 4-6 if necessary

EQUIPMENT NEEDED

- 1: GR 1 Graffiti remover for brick stone concrete
- 2: Safety equipment (chemical resistant gloves, goggles etc)
- 3: long handled roller with quality roller (re-usable if rinsed properly)
- 4: Polypropylene container for dispensing GR1
- 5: Water for applying **before using GR 1 on Painted services**
- 6: pressure washer: we recommend 2200 PSI pressure washer and cold water, in cooler temperatures hot water and higher PSI may be more effective.

Coverage 0.2-0.5 litre/m²

This product is for use by professional contractors and the user guide should be read prior to application



Exterior Graffiti removal process for painted surfaces:

- 1: Put on your protective clothing, safety goggles and gloves
- 2: Check the surface for excess dirt: The surface does not have to be perfectly clean but if there is a lot of traffic film, soot or substantial dirt, it is advisable to clean or power wash this off first.
- 3: Test a small hidden area prior to full application
- 4: **Shake the product thoroughly** to activate it and pour required amount into polypropylene container
- 5: **Spray or apply water to the graffitied area before using the product**
- 6: Apply with brush or roller starting from the bottom up
- 7: wait about 90 seconds then pressure wash off
- 8: repeat steps 4-7 if necessary

**Results and Bene, its
Dramatically reduces the removal time
One application is 99% effective
No damage to underlying surface
No ghosting**

GR 1 GRAFFITI REMOVER IS FOR PROFESSIONAL USE ONLY. NOT TO BE USED FOR ANY OTHER PURPOSE. NOT FOR RESALE. DO NOT MIX WITH ANY OTHER PRODUCT. TRIAL ON A SMALL INCONSPICUOUS AREA PRIOR TO FULL APPLICATION.

- * USE NEAT - DO NOT DILUTE
- * YOU MAY NEED TO WET THE SURFACE PRIOR TO APPLICATION
- * ONLY POUR THE REQUIRED AMOUNT INTO A POLYPROPYLENE CONTAINER
- * DO NOT POUR ANY UNUSED SMART ELITE BACK IN TO CONTAINER AS IT WILL CONTAMINATE THE REST OF THE PRODUCT

EVERY USER OF THIS PRODUCT SHOULD WEAR SAFETY GOGGLES, CHEMICAL RESISTANT GLOVES AND CAREFULLY READ ALL APPLICATION AND SAFETY INSTRUCTION BEFORE USING

Ingestion:	DO NOT induce vomiting, drink 1 - 2 glasses of water, seek medical attention
Skin Contact:	Wash of immediately with plenty of soap and water, Remove contaminated clothing, flush skin with running water. Seek medical attention if irritation or symptoms persist
Eye Contact:	Rinse continuously with water for at least 15 minutes, holding the eyelids open. Seek medical attention. If can be done easily done remove contact lenses.
Spills/leaks:	Absorb on inert absorbent and transfer to container. Prevent spillage from entering natural waters/land drains.
FIRE:	Use water fog or fine water spray. Emergency workers to wear full protective clothing including breathing apparatus.

Emergency contact John Townsend +44 7921 949181

Email sales@graffitimagic.com